

LifePoint™ Deluxe

Meets OSHA Requirements

1926.502(15) and (16)



The LifePoint Deluxe is the perfect fall prevention tie-off point solution for two people when circumstances require non-penetrating versatility. LifePoint provides the answer with an easy to set up and quick-move solution.

Non-Penetrating Versatility:

Protect workers and maintain rooftop water integrity with LifePoint Deluxe. No claws or projectiles to damage the roof surface. The simple weight box design provides OSHA compliance with minimum components to maintain or inspect.

2 Anchorage Capability:

LifePoint Deluxe provides fall protection anchor points for the following:

- (1) person fall restraint and (1) person fall arrest or
- (2) person fall restraint.

Mobility:

LifePoint Deluxe can be repositioned in a few minutes by one person. With the patented pivoting frame design, moving the handle to the transport position, the weight box is lifted and can be easily wheeled to the next location. Then simply move the handle to the work position, the weight box is lowered and the wheels are raised.

Built to Last:

With galvanized and powder coated corrosion resistant components and few moving parts, LifePoint will perform for years.



Two tie-off points.

Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

Lifepoint Duo Features



Move LifePoint Deluxe handle into its travel position. Move unit into position.



Press handle release and lower weights into working position.



Connect lanyard to either fall-restraint or fall-arrest.



Handle release.



Cast weights or cans available.



Flat-free rubber tires.

Options



Optional Lifepoint protective cover.

Specifications

Description	Specifications
Empty weight	200 lbs.
Loaded weight	930 lbs.
Dimensions with handle retracted	70"= (L), 28"= (W), 20"= (H)
Dimensions with handle extended	190"= (L), 28"= (W), 42"= (H)
Tires	Flat Free Solid
Approved surface use:	Poured Concrete, EDPM (adhered & loose laid), TPO (adhered & loose laid), BUR (swept)

Due to continuous improvement, specifications are subject to change without notice.



P : 877.791.4446
E : safetyorders@garlockequip.com
GARLOCKSAFETY.COM

Address:
2601 Niagara Ln N.
Plymouth, MN 55447