

# Permanent Mount Railings

## Meets OSHA Requirements

1926.502(b)(3) and (b)(4), 1910.29(b)(3) and (b)(4)

Permanent guardrail system solutions can be used in many locations, both inside and outside your facility. Permanent guardrail systems can be used for loading docks, stairways, mezzanines or machinery hazard areas. With one of our many base options, we can customize a solution to meet your needs. Available in a variety of colors to match your facility or order them in standard safety yellow.

### Features

- 16 gauge construction welded rail sections that secure to floor or wall areas for permanent applications.
- Standard lengths from 2 to 12 feet. *Custom lengths also available.*
- Safety yellow standard powder coat. Many color options available.
- Multiple base mounting options.



## Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

# Features



**Single Post Floor Mount**



**Double Post Floor Mount**



**Box Floor Mount**



**Zip Base**



**Wrap Over Box Mount**



**Wrap Over Double Post**



**Flush Mount Single Post**



**Flush Mount Double Post**

# Specifications

	Weight (lbs)	Floor Space (in)		Wall Space (in)	
		Width	Length	Width	Height
Single Post Floor Mount	5	5.5	7.5	NA	NA
Double Post Mount	6	5.5	7.5	NA	NA
Box Floor Mount	9	6.5	7.5	NA	NA
Zip Base	2.3	3.25	5.5	NA	NA
Wrap Over Single Post	8	8	6	8	8.75
Wrap Over Double Post	10	9	6	9	8.75
Flush Mount Single Post	8	NA	NA	8	8.75
Flush Double Post	10	NA	NA	10	8.75
Wrap Over Box Mount	10	9	6	9	8.75

- Railing Lengths: 5', 7.5', 10'
- Railing Diameter: 1-5/8"
- Weight: 23-28 lbs



P : 877.791.4446  
E : [safetyorders@garlockequip.com](mailto:safetyorders@garlockequip.com)  
[GARLOCKSAFETY.COM](http://GARLOCKSAFETY.COM)

Address:  
2601 Niagara Ln N.  
Plymouth, MN 55447