

# Cobra Cart™

Mobile fall arrest systems

**Meets OSHA Requirements**

1910.29(b) and 1926.502(b) 926.502(15)  
and (16)

## Features:

- OSHA compliant with third party verification
- Capability for three workers tied off in fall arrest and two in restraint at the same time
- Compatible with a wide range of roof and decking materials, when on 4,000 PSI concrete two can be in restraint and one in arrest
- Integrated handle with brake and towing eye makes it easy to move by one person

## Cobra Cart Standard



## Cobra Cart Deluxe



## OSHA Compliant

Garlock Safety Systems Cobra Cart is third party certified to OSHA standards to ensure maximum safety in elevated work environments. With the capability to accommodate up to three workers tied off in fall arrest and two workers in restraint simultaneously, the Cobra Cart provides unparalleled versatility.

## 5-Person Mobile Anchor Point

When there is a need for a team of workers to be tied off simultaneously for leading edge teamwork, the Cobra Cart is the solution of choice. The Cobra Cart can support up to five workers at the same time, three in fall arrest and two in fall restraint.

## Cobra Cart Deluxe

This versatile cart comes equipped with a spacious toolbox, providing ample storage space for essential tools and equipment. The inclusion of the rear brakes ensures extra stability and control and the SRL tray protects your fall arrest equipment. Further more, the Deluxe Cart offers material handling provisions, allowing for easy transportation of materials and supplies to the worksite.

## Why Choose Garlock?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- 100+ Years of Industry Experience
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

# Features



Integrated handle/brake



Engagement claw



Cobra Cart fall arrest attachment points



Parking brakes (included with Cobra Cart Deluxe, optional on the standard version)



Self retracting lifeline tray (included with Cobra Cart Deluxe, optional on the standard version)



Wide flat free tires exert less pressure on the roof

# Specifications

	Cobra Cart Standard	Cobra Cart Deluxe
Fall Arrest Rating	3 people*	3 people*
Fall Restraint Rating	2 people	2 people
Tool Box	Optional Poly 7.5 ft3"	Standard Steel 8.5 ft3"
Parking Brakes	Optional	Standard
Material Rack	Not Available	Standard
Deck Space - Front	22" x 40"	22" x 40"
Deck Space - Rear	26" x 40"	None
Length (with handle)	102"	102"
Width	59"	59"
Height	36"	52"
Weight	1100 lbs	1100 lbs
Tires	Flat Free 18 x 8.50	Flat Free 18 x 8.50

\*On 4000PSI concrete slab rated for 1 person only  
Due to continuous improvement, specifications are subject to change without notice.

# Cobra Cart Components

301528	Cobra Cart Deluxe	409445	Plastic tool box for Cobra Cart Standard	301088	Parking brake kit for Cobra Cart Standard
301463	Cobra Cart Standard	460-010-003	SLR tray for Cobra Cart Standard		